

Unclassified		/~) l
SECURITY CLASSIFICATION OF THIS PAGE (When	n Date Enfered)	
REPORT DOCUMENTAL		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER		3. RECIPIENT'S CATALOG NUMBER
AFGL-TR-82-0284	AD-A11998	b
4. TITLE (and Subtitle)		5. TYPE OF REPORT & PERIOD COVERED Final Report
STRATOSPHERIC TURBULEN WIND SHEARS	ICE FROM	
WIND SHEARS		5 PERFORMING ORG. REPORT NUMBER
7. AUTHOR(e)		B. CONTRACT OR GRANT NUMBER(#)
Norman Rosenberg		
,		F49620-81-C-0071
9. PERFORMING ORGANIZATION NAME AND AD	DRESS	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
TEL-AVIV University	•	
Research Authority		62101F
Ramat-Aviv, Israel 69978		668705BC
11. CONTROLLING OFFICE NAME AND ADDRESS	5	12. REPORT DATE
Air Force Geophysics Laborat		28 February 1982
Hanscom AFB, Massachusetts	01731	13. NUMBER OF PAGES
Monitor/Earl Good/LKD		7
14. MONITORING AGENCY NAME & ADDRESS(II o	different from Controlling Office)	15. SECURITY CLASS. (of this report) Unclassified
1		Approved for
		l
		15a. DECLASSIFICATION DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)		
Approved for public release; d	istribution unlimited	d
17. DISTRIBUTION STATEMENT (of the abstract of	ntered in Block 20, if different fro	om Report)
18. SUPPLEMENTARY NOTES		
		ELECTER
	•	OOT 77 4000
		OCT 7 1982 ·
19. KEY WORDS (Continue on reverse side if neces	sary and identify by block number	
		A
Stratosphere		A
Winds		

Winds Smoke trails

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

A statistical analysis of smoke trail velocity profiles and balloon velocity profiles has been carried out to evaluate and remove their inherent noise content. The day-to-day variability in the probability of exceeding critical shear was evaluated. The corona anemometer data was compared with the much larger data-base of smoke trail data. Although the corona anemometer showed a higher probability of turbulence, it was within the variability expected from the smoke trail analysis. It is shown that the diffusion integral which

DD 1 FORM 1473 EDITION OF 1 NOV 65 IS OBSOLETE

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

82 10 07 037

CHCTGSSHIER SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered) leads to the diffusion coefficient is very sensitive to the variability in turbulent occurence probabilities. / A collegen F : 7. 1 GMARI 3 GAB -20--೧೯೩೮ ಕ್ಷ Santition towns issien ats. g/ Available and the AVail 1 1 1

> Unclassified SECURITY CLASSIFICATION OF THIS PAGE(When Date Entered)

AFG L-TR-82-0284

TEL-AVIV UNIVERSITY

SCHOOL OF ENGINEERING

Department of Interdisciplinary Studies
University Campus, Ramat-Aviv
69978 Tel-Aviv, Israel



וניברסיטת תל־אביב הפחלקה ללימודים בין־תחומיים קרית האוניברסיטה, רמת־אביב תל־אביב, 69978

STRATOSPHERIC TURBULENCE FROM WIND SHEARS

NORMAN ROSENBERS, PRINCIPAL INVESTIGATOR

FINAL REPORT 28 FEBRUARY 1982

EUROPEAN OFFICE OF AEROSPACE RESEARCH CONTRACT F49420-81-C-0071

ABSTRACT

A STATISTICAL AMALYSIS OF SHOKE TRAIL VELOCITY PROFILES AND BALLOON VELOCITY PROFILES HAS BEEN CARRIED OUT TO EVALUATE AND REMOVE THEIR INHERENT NOISE CONTENT. THE DAY-TO-DAY VARIABILITY IN THE PROBABILITY OF EXCEEDING CRITICAL SHEAR WAS EVALUATED. THE CORONA AMENOMETER DATA WAS COMPARED WITH THE MUCH LARGER DATA-BASE OF SHOKE TRAIL DATA. ALTHOUGH THE CORONA AMEMOMETER SHOWED A HIGHER PROBABILITY OF TURBULENCE, IT WAS WITHIN THE VARIABILITY EXPECTED FROM THE SHOKE TRAIL AMALYSIS. IT IS SHOWN THAT THE DIFFUSION INTEGRAL WHICH LEADS TO THE DIFFUSION COEFFICIENT IS VERY SENSITITIVE TO THE VARIABILITY IN TURBULENT OCCURENCE PROBABILITIES.

STRATOSPHERIC TURBULENCE FROM WIND SHEAPS

MORNAN ROSENBERS, PRINCIPAL INVESTIGATOR FACULTY OF ENGINEERING TEL AVIV UNIVERSITY RAMAT AVIV ISRAEL

FINAL REPORT 28 FEBRUARY 1982

EUROPEAN OFFICE OF AEROSPACE RESEARCH CONTRACT F49620-81-C-0071

CONTENTS

- 1. INTRODUCTION
- 2. BACKGROUND
- J. DATA SOURCES
- 4. DATA PROCESSING
- S. DISCUSSION OF RESULTS
- 4. CONCLUSIONS
- 7. REFERENCES
- 8. TABLES
- 9. FIGURES

INTRODUCTION

THE OCCURENCE OF TURBULENCE IN THE PREDOMINANTLY-LAMINAR STRATOSPHERE IS IMPORTANT IN BEFINING HODELS FOR DISPERSAL OF STRATOSPHERIC POLLUTANTS AND FOR SCATTERING OF EN WAVES SUCH AS LASER BEAMS. STATISTICAL ESTIMATES OF FREQUENCY OF OCCURRENCE OF VERTICAL SHEARS IN THE HORIZONTAL WIND SUFFICIENTLY HIGH TO CAUSE TURBULENCE HAVE BEEN HADE FROM BROUND-BASED OBSERVATION OF SMOKE TRAILS RELEASED FROM ROCKETS AND FROM BALLOON-BORNE SENSORS SUCH AS THE CORONA ANEMOMETER BEVELOPED AND FLOWN BY AFGL SCIENTISTS. THE PRESENT STUDY COMPARES RESULTS FROM THE TWO TYPES OF MEASUREMENTS WITH PARTICULAR ATTENTION TO THE APPROPRIATE STATISTICAL TREATMENT OF THE ORIGINAL BATA AND AM ESTIMATE OF THE VARIABILITY OF RESULTING IMPUTS TO ATMOSPHERIC MODELS.

BACKGROUND

EARLIER REPORTS BY AFGL SCIENTISTS (REF 1) DESCRIBED PROCESSING OF 200 SHOKE TRAILS MADE BY MASA SCIENTISTS. THE CORONAM (CORONA AMENOMETER) PROFILES OBTAINED IN AFSL EXPERIMENTS WERE DESCRIBED IN A FINAL REPORT (REF 2) UNDER OUR PREVIOUS CONTRACT. THE PRESENT STUDY REVIEWS THE DATA TREATMENT MADE IN THE EARLIER REPORTS AND REPORTS SIGNIFICANTLY-DIFFERENT CONCLUSIONS OBTAINED BY FURTHER STATISTICAL CONSIDERATIONS.

The state of the s

BATA SOURCES

THE BATA SOURCES ARE DESCRIBED IN REF 1 AND REF 2. THE 200 MASA SMOKE TRAILS WERE TAKEN RANDONLY WITH RESPECT TO TIME AND SEASON. ALL WERE TAKEN BURING DAYLIGHT HOURS AND ONLY UNDER CLOUD-FREE CONDITIONS. THE AFGL BALLOON FLIGHT ANALYSED WAS TAKEN IN APRIL 1977 FROM 0500 TO 1400 LOCAL TIME. THEREFORE NO IMPERENCE CAN BE MADE AS TO STATISTICS WHICH RELATE TO DISTURBED WEATHER OR DIURNAL EFFECTS.

THE NASA SHOKE PROFILES WERE AVAILABLE AS DIGITAL TAPES, REPORTED AS NORTH AND EAST VELOCITY COMPONENTS TO 0.1 M/S AT VERTICAL SPACING OF 25 HETERS. NO ACCURACY ESTINATES WERE AVAILABLE ON THE HEASUREHENTS.

THE AFBL CORONAH PROFILES WERE AVAILABLE ON DIGITAL TAPES WHICH REPORT AT 10-SECOND INTERVALS. REPORTING PRECISION IS NOT AN ACCURACY ESTIMATE.

- 1. GHT TIME TO 1 SECOND
- 2. RADAR BALLOOM POSITION TO 1 NETER IN NORTH, EAST, AND ALTITUDE.
- 3. CORDNAM VELOCITY (RELATIVE TO BALLOON) TO 0.1 M/S AND DIRECTION TO 0.1 DEGREE.
- 4. TEMPERATURE AND PRESSURE.

THE SHOKE TRAILS WERE REPORTED BETWEEN 5 AND 20 KM AND THE CORONAM FLIGHT CONTAINED 5 UP OR DOWN 'LEGS' BETWEEN 17 AND 25 KM ALTITUDE.

THE MASA SHOKE PROFILES WERE DIRECTLY AVAILABLE AS EAST AND NORTH VELOCITY COMPONENTS. IN THE PRESENT STUDY, 75 SHOKE TRAILS WERE USED WITH THE ANALYSIS BEING HADE ON SEPARATE SEGMENTS BETWEEN 8 AND 13 KM (CONSIDERED TROPOSPHERIC) AND BETWEEN 13 AND 18 KM (CONSIDERED STRATOSPHERIC). SINCE NO TEMPERATURE DATA WAS AVAILABLE, TEMPERATURE PROFILES WERE TAKEN AS US STANDARD ATHOSPHERE VALUES. VALUES OF TEMPERATURE AND GRADIENT OF -6.5 DEG/KM IN THE TROPOSPHERE AND 0 DEG/KM IN THE STRATOSPHERE LED TO CRITICAL SHEARS FOR TURBULENCE OF 22 M/S/KM AND 45 M/S/KM RESPECTIVELY.

THE PROCESSING TO CONVERT CORONAM DATA TO EAST AND NORTH VELOCITY COMPONENTS AT 20 NETER VERTICAL SPACING HAS BEEN BESCRIBED IN REF 2. TEMPERATURE PROFILES USER AVAILABLE SO LOCAL VALUES OF CRITICAL SHEAR COULD BE COMPUTED AND THE LOCAL SHEAR RELATED TO THIS VALUE RATHER TO A STANDARD VALUE. IT SHOULD BE NOTED THAT THE LOCAL TEMPERATURE PROFILE SHOWED A DOUBLE HAXINUM AND A RANGE OF CRITICAL SHEARS BETWEEN 35 AND 55 N/S/KM, STRADDLING THE STANDARD ATMOSPHERE VALUE OF 45 N/S/KM.

THUS LOCAL VELOCITY COMPONENTS AND LOCAL CRITICAL SHEAR VALUES WERE AVAILABLE FOR DOTH SETS OF DATA FOR FURTHER PROCESSING.

ABOUT 10000 POINTS WERE AVAILABLE FROM 75 SMOKE TRAILS AVAILABLE AT STRATOSPHERIC ALTITUDES. THE CORONAN PROFILES CONTAINED ABOUT 1000 POINTS AMONG THE 5 LEBS WHICH WERE CONSIDERED AS SEPARATE 'TRAILS'.

DATA PROCESSING

THE RELEVANT CARCABLE FOR TURBULENCE IS THE RATIO OF THE LOCAL VERTICAL SHEAR OF THE HORIZONTAL VELOCITY TO THE LOCAL CRITICAL SHEAR.

CRITICAL SHEAR IS DEFINED (REF 1) IN RECIPROCAL SECONDS AS

CRIT SHEAR = 2. + GRAV/TEMP + [BTDZ - DTDZ ADIAB]

IT IS CONVENIENT TO EXPRESS THIS IN UNITS OF NET/SEC/KM = 1000+ THE ABOVE VALUE. CRITICAL SHEARS RANGE FROM 20 M/S/KM IN THE TROPOSPHERE TO 50 M/S/KM IN THE STRATOSPHERE, DEPENDING ON LOCAL TEMPERATURE GRADIENT.

BETWEEN VELOCITY VALUES, AN IMPORTANT PROBLEM IS TO RELATE TO THE IMMERENT NOISE CONTENT RELATIVE TO SIGNAL. THE AVERAGE RMS DIFFERENCE BETWEEN ADJACENT PDINTS BEPARATED BY 20-25 METERS WAS ABOUT 0.6 M/S. SPATIAL FREQUENCY ANALYSIS BY FOURIER TRANSFORM SHOWED A VELOCITY RMS AMPLITUDE OF 3 M/S AT THE MYQUIST FREQUENCY (CORRESPONDING TO A SPATIAL WAVELENGTH OF 40-50 METERS). A LARGE FRACTION OF THIS AMPLITUDE IS THEREFORE A RANDOM VELOCITY ERROR WHICH IS PRESENT AT ALL SPATIAL FREQUENCIES. REDUCTION OF THIS NOISE CONTENT CAN BE ATTEMPTED BY ONE OF THREE FILTERS

- 1. ASSUME THAT THE AVERAGE ENERGY CONTENT AT MEAR-NYQUIST FREQUENCIES IS UNITE NOISE. REMOVE THIS ESTIMATED NOISE ENERGY FROM ALL FREQUENCIES. BACK TRANSFORM TO OBTAIN A FILTERED VELOCITY PROFILE.
- 2. ESTABLISH THE POWER DEPENDENCE OF AMPLITUDE VS SPATIAL FREQUENCY FROM LOWER-FREQUENCY AMPLITUDES, AND RESTRICT HIGH FREQUENCY AMPLITUDES NOT TO EXCEED THE POWER LAW. RETRANSFORM TO A FILTERED VELOCITY PROFILE.
- 3. AFPLY A SMOOTHING FUNCTION TO THE ORIGINAL VELOCITY PROFILE TO REDUCE THE HIGH-FREQUENCY CONTENT, DIRECTLY PROVIDING A FILTERED VELOCITY PROFILE.

HAVE A SHALLER EFFECT ON DIFFERENCES DETUEN POINTS WITH HIGHER SEPARATIONS. HOWEVER, ALL REDUCE THE NOMINAL RESOLUTION OF 20-25 METERS TO A POORER RESOLUTION. THE RHS DIFFERENCE DETUEN ORIGINAL AND FILTERED PROFILES USING ANY OF THE THREE FILTERS WAS ONLY ABOUT 0.2 M/S ALTHOUGH EACH REDUCED THE HIGH FREQUENCY AMPLITUDE VALUES TEN-FOLD FROM 3 M/S TO 0.3 M/S.

A 3-POINT RUNNING AVERAGE WAS SELECTED AS THE SIMPLEST FILTER BECAUSE IT MAKES NO ASSUMPTION OF THE VALIDITY OF THE POWER-LAW DEPENDENCE OR THE WHITE-NOISE NATURE OF THE VELOCITY ERRORS. AS WILL BE SEEN BELOW FROM GRAPHS OF AMPLITUDE US FREQUENCY, NEITHER ASSUMPTION IS VALID FOR A SINGLE TRAIL, ALTHOUGH BOTH MAY BE VALID TO THE AMPLITUDES AVERAGED OVER A NUMBER OF PROFILES.

BEFORE THIS FILTER WAS APPLIED, A STATISTICAL TEST WAS USED TO REJECT GROSS OUTLIER POINTS FROM CONSIDERATION. THE 50 PERCENTILE RMS DIFFERENCE BETWEEN ABJACENT POINTS WAS ABOUT 0.6 M/S AND THE 95 PERCENTILE WAS ABOUT 1.0 M/S. ANY POINTS WHICH SHOWED DIFFERENCES GREATER THAN 2 M/S FROM THEIR ADJACENT NEIGHBORS WERE TREATED AS GROSS ERRORS, AND IGNORED. TWO TYPES OF OUTLIERS WERE FOUND-

- 1. M/S= 1.0 1.1 1.3 6.2 6.3 6.5.... WHERE A 'STEP' IS PRESENT
- 2. M/S= 1.0 1.1 6.2 1.3 1.1... WHERE A SINGLE OUTLIER IS PRESENT.

NEITHER TYPE OF OUTLIER IS CONSIDERED POSSIBLE OVER A 20 METER SPACING AND SO BOTH TYPES WERE PRE-EDITED OUT OF THE BATA. OUTLIERS OCCURED VERY INFREQUENTLY, ABOUT 80 PCT OF THE SHOKE TRAILS SHOWED NONE, AND ONLY 3 TRAILS SHOWED HORE THAN 5 OUTLIERS IN 200 POINT SAMPLES. THESE TRAILS WERE REJECTED. IN THE CORONAN PROFILES, A TOTAL OF 20 OUTLIERS WERE FOUND IN 1000 TOTAL POINTS AND WERE EDITED OUT. FOLLOWING THIS PRE-EDITING, THE RUNNING AVERAGE WAS USED TO PRODUCE EACH FILTERED PROFILE.

FIGURE 1 SHOWS A SINGLE CORONAN VELOCITY COMPONENT PROFILE BEFORE AND AFTER FILTERING. IT ALSO SHOWS THE BALLOON VELOCITY PROFILE DERIVED FROM THE RADAR TRACK. THE SINILARITY BETWEEN THE PROFILES IS STRIKING. NO NICH-FREQUENCY CONTENT IS PRESENT IN THE BALLOON PROFILE, BUT IS ADDED BY THE CORONAN DATA AND IS THEN PARTIALY REMOVED BY THE FILTER.

and the same

A STATE OF THE PARTY OF

FIGURE 2 SHOWS THE DIFFERENCE BETWEEN RAW AND FILTERED VELOCITIES FOR A SINGLE COMPONENT AND THE ABJACENT-POINT TOTAL SHEARS FOR RAW AND FILTERED PROFILES.

FIGURE 3 SHOWS FOURIER AMPLITUDES DEFORE AND AFTER FILTERING FOR (1) A SINGLE VELOCITY COMPONENT AND (2) FOR AVERAGE AMPLITUDES FOR ALL 10 CORONAM COMPONENTS (5 LEGS X 2 DIRECTIONS)

TABLE 1 AND FIGURE 4 PRESENTS THE PROBABILITY OF EXCEEDING A SIVEN SHEAR VS SHEAR AT 20-25 METER SPACING. THE TWO DATA SETS ARE THE STRATOSPHERIC PORTION OF THE SMOKE TRAILS AND THE 5 CORONAN LEGS.

TABLE 2 AND FIGURE 5 SIMILARLY PRESENTS PROBABILITY OF EXCEEDING A GIVEN RATIO OF SHEAR/CRITICAL SHEAR VS THIS RATIO.

FIGURE 6 PRESENTS PROBABILITY OF EXCEEDING GIVEN FRACTION OF CRITICAL SHEAR. THIS WAS GENERATED FOLLOWING THE PROCEDURE DESCRIBED IN REFERENCE 1. THE PROBABILITY OF EXCEEDING THE CRITICAL SHEAR WAS FOUND FOR LAYER THICKNESSES RANGING FROM THE CLOSEST SPACING (20-25 METERS) TO INCREASED ALTITUDE DIFFERENCES UP TO 400 METER LAYER THICKNESS. AS SHOWN IN FIGURE 6, PROBABILITIES OF EXCEEDING CRITICAL SHEAR AT LAYER THICKNESS OF 100 METERS RANGE FROM ABOUT 10 PCT IN UNFILTERED CORONAM TRAILS TO ABOUT 2 PERCENT IN FILTERED SHOKE PROFILES.

FIGURE 7 WAS ALSO PREPARED FOLLOWING THE PROCEDURE OF REFERENCE 1. THE INTEGRAL OF PROB(L) * L * L IS A DIFFUSION PARAMETER WITH DIMENSION M2. THIS PARAMETER, WHEN DIVIDED BY THE ESTIMATED LIFETIME OF A TURBULENT EDDY, (1000-3000 SECONDS) WAS SHOWN IN REF 1 TO BE A MEASURE OF THE EFFECTIVE DIFFUSION COEFFICIENT IN THE STRATOSPHERE. FIGURE 7 PRESENTS A PLOT OF THE CONTRIBUTION TO THE PARAMETER FROM ALL LAYER THICKNESS UP TO THICKNESS L VS LAYER THICKNESS L. AS CAN BE SEEN, THE CONTRIBUTION OF THIN LAYERS IS TRIVIAL, AND THE MAJOR CONTRIBUTION IS ONLY FROM LAYER THICKNESSES ABOVE 100 METERS. THE FINAL PARAMETER VALUES AT 400 METER SPACING ARE WITHIN A FACTOR OF 3 FOR ALL 4 DATA SETS.

DISCUSSION OF RESULTS

THE DIFFERENCES DETUEEN SMOKE AND CORONAN PROBABILITIES ARE SUBSTANTIAL, BUT NOT NECESSARILY STATISTICALLY SIGNIFICANT.

TO TEST SIGNIFICANCE, THE PROBABILITIES WERE SEPARATELY COMPUTED FOR EACH OF THE SHOKE PROFILES, WHICH PERHITTED A CALCULATION OF THE STANDARD DEVIATION AHONG THE 73 PROFILES FOR EACH PROBABILITY ESTIMATE.

TABLE 3 PRESENTS THE RESULT OF THIS CALCULATION. COLUMN 1 SHOWS LAYER THICKNESS AND COLUMN 2 THE AVERAGE NUMBER OF POINTS PER TRAIL. THE FOLLOOWING COLUMN PAIRS SHOW THE AVERAGE PROBABILITY (AMONG 73 TRAILS) OF EXCEEDING A GIVEN RATIO OF SHEAR/CRIT SHEAR AND THE STANDARD DEVIATION OF THIS AVERAGE. FOR EXAMPLE, CONSIDER THE VALUES FOR EXCEEDING A CRITICAL SHEAR OF 1. THE 25 METER LAYER THICKNESS HAS AN AVERAGE OF 3.99 PCT AND A STDV OF 3.36 PCT. THE 250 METER LAYER THICKNESS HAS AN AVERAGE 0.35 PCT WITH A STDV OF 1.12 PCT. THE DISTRIBUTION IS GENERALLY POISSON (AVG=STBV) FOR PROBABILITIES BELOW 10 PCT, AND STANDARD DEVIATIONS ARE SEVERAL TIMES LARGER THAN AVG FOR PROBABILITIES BELOW 3 PCT.

THE STANDARD DEVIATION IS A MEASURE OF DAY-TO-DAY VARIABILITY. IT SUGGESTS THAT
THE COROMAN SHEARS, ALTHOUGH HIGHER THAN THE AVERAGE SMOKE PROFILES, ARE WITHIN
THE EXPECTED VARIABILITY OF STRATOSPHERIC TURBULENCE.

THIS VARIABILITY SERIOUSLY AFFECTS THE ESTIMATED DIFFUSION PARAMETER. THIS PARAMETER IS BOHINATED BY LAYER THICKNESSES ABOVE 100 METERS, WHICH HAVE LOW PROBABILITIES, BUT IF THE VARIABILITY IS AS HIGH AS SHOWN, INCREASED PROBABILITIES OF THICK LAYERS WILL NOT BE INFREQUENT.

A TEST WAS MADE OF THE SENSITIVITY OF DIFFUSION PARAMETER, BY TAKING THE 0.8 AMB 1.2 CRITICAL-RATIO PROBABILITY VALUES INSTEAD OF THE 1.0 RATIO VALUES. THE DIFFUSION PARAMETER INCREASED AND DECREASED BY FACTOR OF 3 BY THIS 20 PCT SHIFT IN DEFINITION OF CRITICALITY, WHICH WILL CERTAINLY OCCUR WITH THE DAY-TO-DAY VARIABILITY FOUND.

CONCLUSIONS

- 1. THE CONTRIBUTION TO THE DIFFUSION COEFFICIENT FROM LAYERS OF LESS THAN 100 METERS THICKNESS IS NEGLIGIBLE. EFFORTS TO INCREASE RESOLUTION TO OBTAIN 'BETTER' ESTIMATES OF DIFFUSIVITY ARE THEREFORE NOT WORTHWHILE.
- 2. NOISE REDUCTION BY FILTERING WITH A RUNNING AVERAGE REDUCES HIGH FREQUENCY AMPLITUDES BY A FACTOR OF 10, FROM ABOUT 3.0 M/S TO 0.3 M/S (PER UNIT FREQUENCY). THIS FILTER HAS ONLY A SMALL EFFECT ON ACTUAL VELOCITIES, RESULTING IN AN RMS CHANGE OF ONLY 0.2 M/S. THE FILTER REDUCES THE COMPUTED DIFFUSION INTEGRAL BY ABOUT 30 PCT.
- J. THE DAY-TO-DAY VARIABILITY OF THE PROBABILITY OF EXCEEDI TRITICAL SHEAR IS HIGH RELATIVE TO THE LOW-PROBABILITY LARGE THICKNESSES ICH CONTROL THE DIFFUSION PARAMETER. IN FACT, THE ENTIRE FILTERING PROCES. UCH SMALLER IN ITS EFFECT THAN THE DAY-TO-DAY VARIABILITY EFFECT. COMBINED WITH THE UNCERTAINTY OF TURBULENCE LIFETIME, IT WOULD APPEAR THAT ANY DIFFUSION CONSTANT ESTIMATE WILL HAVE AN UNCERTAINTY OF AN ORDER OF MAGNITUDE.
- 4. THE CORONAH MEASUREMENTS OF SHEAR PROBABILITY ARE HIGH WITH RESPECT TO THE AVERAGE OF THE SMOKE TRAIL VALUES, BUT ARE WITHIN THE 95 PCT CONFIDENCE LIMITS. IN OTHER WORDS, THE CORONAM RESULTS HIGHT BE EXPECTED IN 1 DAY EVERY 20.

REFERENCES

- 1. ROSENBERG N.W. AND E.M. BEWAN, STARTOSPHERIC TURBULENCE AND VERTICAL EFFECTIVE DIFFUSION COEFFICIENTS', CIAP CONFERENCE (1974)
- 2. ROSEMBERG N.W. 'STRATOSPHERIC RESIDENCE TIMES', FINAL REPORT UNDER USAF CONTRACT AF-47620-B1-80-C-0071 TEL UNIVERSITY (1981)

and the same of th

1. PROBABILITY OF EXCEEDING GIV SHEAR VS LAYER THICKNESS (PROBABILITY PER 10000 POINTS)

SHEAR M		10	20	30	40	50	60	70	80	90	100	110
LAYER ME	PIS	PROB										
İ	۲-	ľ	RAL	I SMOI								
25	11472	7421	3591	1409	798	537	365	248	141	59	0	0
50	11399	7584	3230	1254	641	321	185	115	61	24	0	0
75	11326	7261	2948	1068	484	227	113	50	21	7	0	0
100	11253	7130	2745	947	378	155	62	20	8	3	0	0
125	11180	5884	2472	804	287	93	32	13	4	0	0	0
250	10815	5918	1509	362	60	10	0	0	0	0	0	0
375	10450	4887	931	131	1.4	0	0	0	0	0	0	0
	ŀ		FIL	TERE	I SMOK	E TRA	ILS					
25	11472	7255	2947	: 357	49.3	227	113	50	21	,	0	. 0
50	11399	/188	2832	1000	428	198	91	34	10	3	0	٥
75	11326	7058	2637	891	371	165	57	22	7	0	0	Э
100	11253	6901	2440	919	313	103	39	12	5	0	0	0
125	11180	5733	2257	220	238	74	21	8	2	0	0	0
250	10815	5810	1405	347	55	5	0	0	0	0	9	0
3.75	10450	4933	901	122	11	0	0	0	0	0	0	0
	[ETI	TERE	o cord	NAM T	SATE	<u>.</u>				
20	955	8819	5487	3876	2052	1026	446	! 175	21	0	0	0
40	940	8768	6229	3535	1750	750	271	73	0	Ö	ō	Ŏ
60	955	3:07	±042	3173	1330	565	157	31	Ö	0	Ö	Ö
30	950	8495	5674	2642	968	368	84	21	0	0	ű	Ö
100	945	3423	5323	2138	741	190	53	0	0	0	ō	Õ
200	920	7902	4000	609	9.7	9	0	0	0	ŏ	Ö	0
300	391	1251	2425	123	C.	0	0	Q	0	0	3	ŏ

TABLE 2. PROPABILITY OF EXCEEDING GIVEN RATIO OF "MEAR/CRITICAL SHEAR VS LAYER THICKNESS

SHR/CRI	<u>T ShR=</u>	2	4	.5	. 3	1.0	1.2	1.3	1.5	1.8	2.0	2.2
LAYER M	ET PTS	กหอษ						***				
	الم		نفذ	/ Sm0:	(E TRA	TLS						
25	11472	8335	4495	1285	1143	/29	520	375	284	135	95	44
50	11399	3075	4353	1941	9/5	550	309	199	128	82	39	2:
75	11326	7915	4071	1639	791	411	216	124	64	33	1.2	
100	1:253	7803	3338	1425	355	316	149	67	29	14	วั	
125	11130	7635	3583	1298	537	238	89	33	13	ó	2	1
250	13815	:351	2452	592	200	4 4	6	0	0	0	O	1
		1										

-	250	10815	:851	2452	492	300		6	-	0	0	-	7	1
	375	10450	5928	1590	371	60	5	0	0	0	0	0	0	
	1	1 1											1	
- 1	1	1		Eli	<u> 1585</u>	<u> 2,538</u>	CE TRA	ALLS						
ı	25	11472	7919	40.75	1539	./39	411	216	124	63	32	12]	
	50	11399	2859	3922	155;	238	355	195	100	45	22	7	3	
ı	75	11326	7,199	3.753	1425	553	321	155	63	30	12	4	0	
- }	190	11253	2658	3557	1297	542	248	96	42	15	7	1	0	
١	1.25	11180	7521	1365	1187	451	195	21	23	10	3	0	0	
[250	10815	6775	2382	658	178	40	4	0	0	0	0	0	
- [375	10450	5895	1544	355	5.1	5	0	0	0	0	0	ာ	
1													ļ	
ł]		EI	JERE	2 0080	nan 1	TRAILS					}	
-	20	965	9119	2131	5098	3109	1927	1067	560	259	93	41	0	
]	40	960	8440	5396	4823	2927	1656	750	354	127	63	10	ol	
J	60	955	8942	5817	4576	2440	1267	545	241	105	31	0	اه	
ı	80	950	3747	5526	4137	2000	832	337	189	53	11	Ō	اه	
1	100	945	9.751	:370	3577	1714	514	296	138	11	0	ō	0	
-	200	920	8196	5130	2098	533	163	22	0	Ö	ā	ō	o l	
1	300	345	2754	3855	1050	156	22	0	0	Ö	Ō	9	ō	
					•			_	_	-	-	-		


,4+

TABLE 3 PROBABILITY OF EXCEEDING GIVEN RATTO OF SHEAR/CRIT SHEAR FOR 73 FILTERED SMOKE PROFILES. COLUMN PATRS ARE AMONG-TRAIL


c
2
~
10000
2
Ç
<u> </u>
>
Ξ
-
₹
3
Ξ
٥.
AS PROBABILITY PER
_
APIKE SSED
್ತು
ران درد
¥
÷
0
z
\equiv
_
Æ
>
ND DEVIATIONS
\Box
¥
2
Z
Ŧ
J STANDARI
=
Ž
S AND STANDARI
တ
Ä
₹
2
5
AVERAGES


. 8	22.22.00
	35 20 20 20 20 20 20 20 20 20 20 20 20 20
9.1	25 25 25 35 35 35 35 35 35 35 35 35 35 35 35 35
	24 C) - 2 A B O O
-	147 105 105 105 105 105
	238 24 24 24 24 24 24 24 24 24 24 24 24 24
F-4	128 148 158 158 158 158 158
	188 188 150 150 150
0	333 13 13 13 13 13 13 13 13 13 13 13 13

60	300 A 4 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 5 500 50
	2 2 4 2 4 2 4 2 4 2 4 2 4 2 4 2 4 2 4 2
3.	4 1 M 4 M 4 M 4 M 4 M 4 M 4 M 4 M 4 M 4
	1601 1513 1258 1152 637 362
•	1252 1285 1296 1220 1249 1271
	4019 3869 3707 3500 3313 2311
2.	1021 4019 1029 3869 1043 3707 1107 3500 1159 3313 1510 2311
HCR=	25 157 7889 50 156 7821 75 155 7777 100 154 7627 125 153 7494 250 148 6733 375 143 5849
SH/SHCR=	1557 1557 1558 1588 1588 1588
	25 25 125 250 375



5 77/5










FIGURE 6 PROBABILITY OF EXCEEDING RATIO SHR/CRIT = 1



LAYER THICKNESS, METERS

 $\int_{0}^{\infty} P(I_{c}) \cdot L^{2} dI_{c}$ DIFFUSION PARAMETER VS LAYER THICKNESS L FICURE 7



LAYER THICKNESS, METERS

END

DATE FILMED



DTIC